



# FRESCO Ultra Boost

## (PAO 0W20)

### Product Description:

FRESCO Ultra Boost is a premium fully synthetic engine oil for passenger car, formulated with top grade polyalphaolefin PAO synthetic base fluid and new additives technology to meet the latest industry standards of API SP and ILSAC GF-6 for newer engines including turbocharged gasoline direct injection (TGTDI) engines.

TGTDI engines require increased protection against Low-Speed Pre-Ignition (LSPI) and timing chain wear. LSPI is common issue with turbocharged engines, it creates excessive pressures inside the engine's cylinder, which can cause engine damage. FRESCO Ultra Boost is specifically designed to mitigate LSPI and provide timing chain wear protection.

The benefits of PAO synthetic base stocks include excellent high viscosity index with low temperature fluidity and high resistance to oxidation as well as thermal degradation. These properties make PAO a good selection in temperature extremes, including high operating and low start-up temperatures.

### Applications / Benefits:

- Particular suitable for the modern engine.
- Timing chain wear protection.
- Minimize the occurrence of LSPI.
- Better fuel economy and fuel efficiency.
- Improve wear and deposit control of the engine.
- Enhance piston cleanliness while maintaining sludge control.

### Typical Characteristics:

Test Description	Method	
SAE Viscosity Grade	SAE J 300	<b>0W20</b>
Specific Gravity @ 15°C	ASTM D 4052	0.855
Flash Point, °C	ASTM D 92	212
Pour Point, °C	ASTM D 97	-42
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	43.69
cSt @ 100°C	ASTM D 445	8.749
Viscosity Index	ASTM D 2270	185
TBN, mgKOH/g	ASTM D 2896	7.0
Color	ASTM D 1500	<3.0
CCS, cP	ASTM D 5293	≤6200
HTHS, cP	ASTM D 5481	≥2.6

### Suggested for the following uses:

- API SP
- ILSAC GF-6
- Ford WSS-M2C962-A1\*
- Ford WSS-M2C963-A1\*\*

\* Please note official claim apply to SAE 0W20, only

Product Data Sheet

Furnishing the information contained herein does not constitute a representation by FRESCO that any product or process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of FRESCO or any third party. FRESCO assumes no liability for any infringement which might arise out of the product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses FRESCO warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS OR IMPLIED including but not limited to warranties of MERCHANTABILITY and FITNESS.