



FRESCO Ultra Performance

(PAO 5W40)

Product Description:

FRESCO Ultra Performance Fully Synthetic Engine Oil is blended from a synthesis of special basestock processed by a patented technology. Reinforced with a powerful additive package, as well as having Polyalphaolefins (PAO) content, FRESCO Ultra Performance is ideal for modern high output, low emission, super or turbo charged, DOHC or GDI engines that are commonly found in latest, European, Japanese and Korean models.

With a natural High Viscosity Index and low volatility, FRESCO Ultra Performance offers high performances, uncompromised protection to the engines. Due to its excellent anti oxidation property, FRESCO Ultra Performance Fully Synthetic Engine Oil exhibits much extended drain interval and potential fuel saving.

FRESCO Ultra Performance Fully Synthetic Engine Oil meets highest API standard for gasoline engine and is suitable for using in the widest range of modern Passenger Cars and small vehicles.

Applications / Benefits:

- Super fluidity over a wide range of temperatures and operating conditions.
- Improves engine performance, yet energy conserving.
- Superior high temperature protection.
- Protects against rust and corrosion, extend drain interval.

Typical Characteristics:

Test Description	Method	
SAE Viscosity Grade	SAE J 300	5W40
Specific Gravity @ 15°C	ASTM D 4052	0.855
Flash Point, °C	ASTM D 92	216
Pour Point, °C	ASTM D 97	-42
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	86.92
cSt @ 100°C	ASTM D 445	14.36
Viscosity Index	ASTM D 2270	172
TBN, mgKOH/g	ASTM D 2896	7.8
Color	ASTM D 1500	<2.5
CCS, cP	ASTM D 5293	5520

Specifications, Approvals & Recommendations:

- API SP/SM/SL/CF
- ACEA C3-16
- BMW Longlife - 04
- MB-Approval 229.51
- Porsche A40
- PSA B71 2290
- Renault Rn0700/RN0710
- VW 502 00/505 01

Product Data Sheet

Furnishing the information contained herein does not constitute a representation by FRESCO that any product or process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of FRESCO or any third party. FRESCO assumes no liability for any infringement which might arise out of the product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses. FRESCO warrants only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTIES relating to the products and the application thereof. EXPRESS OR IMPLIED including but not limited to warranties of MERCHANTABILITY and FITNESS.