

FRESCO Ultra Shield (10W40 Semi Synthetic)

Product Description:

Passenger car motor oil (PCMO) delivers the latest development of lubricating oil technology to maximize protection for the newest gasoline fueled engines. It meets the highest performance level of API SP and exceeds the most demanding requirements of modern engine's emission control and oil consumption standards. In today's energy conscious era, this oil is also formulated to improve fuel efficiency for consumers.

Applications / Benefits:

- Exceeds the highest U.S Lubricating oils standards for gasoline and LPG/CNG engines.
- Silky smooth operation for all high performance engines.
- Increases emission system durability and improves fuel efficiency.
- · Improves piston cleanliness and increases engine sludge protection.

Typical Characteristics:

Test Description	Method	Unit	
SAE Viscosity Grade	SAE J 300	-	10W40
Density @ 15 °C	ASTM D 4052	kg/L	0.8580
Flash Point	ASTM D 92	°C	218
Pour Point	ASTM D 97	°C	-33
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	97.9
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	14.8
Viscosity Index	ASTM D 2270	-	159
TBN	ASTM D 2896	mgKOH/g	7
ccs	ASTM D 5293	сР	4833

Specifications, Approvals & Recommendations:

• API • SP

Furnishing the information contained herein does not constitute a representation by FRESCO that any product or process is free from patent infringement claims of any third party nor does it constitute the granting of a license under any patent of FRESCO or any third party. FRESCO assumesno liability for any infringement which might arise out of the product. The information and suggestions for use and application presented herein represent the best information available to us and believed to be reliable. They should not, however, be construed as controlling suggestions, and users urged to conduct confirmatory test to determine final suitability for their specific end uses FRESCO warranty only that its products meet the specifications which it sets for them and specifically DISCLAIMS ALL OTHER WARRANTS relating to the products and the application thereof. EXPRESS or IMPLIED including but not limited to warranties of MERCHANTABLITY and FITNESS.

^{*} Please note official claim apply to SEMI SAE 10W40 only